

HYDRAULIC DEEPDRAWING PRESS, TRYOUT PRESS 油圧式深絞り成型機、トライプレス機

SLS SERIES

Safe Production, Unique Hydraulic Circuit,
Durability, High Accuracy

安全な生産、独立の油圧回路、
耐久そして持続的な精度



| Module No. 型式 | Unit 単位 | SLS-100D | SLS-150D | SLS-200D | SLS-250D | SLS-300D | SLS-400D | SLS-500D | SLS-600D | SLS-800D | SLS-1000D | SLS-1200D | SLS-1500D |
|----------------------------------|------------|-----------|------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| Capacity 能力 | ton | 100 | 150 | 200 | 250 | 300 | 400 | 500 | 600 | 800 | 1000 | 1200 | 1500 |
| Table Size テーブル面積 | mm | 800 x 700 | 1000 x 850 | 1000 x 1000 | 1200 x 1000 | 1500 x 1200 | 1800 x 1300 | 2000 x 1500 | 2500 x 1500 | 2500 x 1800 | 3000 x 2000 | 3200 x 2000 | 3500 x 2000 |
| Open Height オープンハイト | mm | 650 | 800 | 950 | 950 | 1100 | 1200 | 1200 | 1200 | 1400 | 1600 | 1600 | 1600 |
| Stroke ストローク | mm | 500 | 600 | 700 | 700 | 800 | 800 | 900 | 900 | 1000 | 1200 | 1200 | 1200 |
| Lifting Capacity 引き上げ能力 | ton | 7 | 9 | 12 | 15 | 20 | 28 | 30 | 35 | 40 | 50 | 55 | 60 |
| Quick Descending Speed 高速下降速度 | mm / sec | 300-350 | 300-350 | 300-350 | 300-350 | 300-350 | 300-350 | 300-350 | 300-350 | 300-350 | 300-350 | 300-350 | 300-350 |
| Slow Descending Speed 低速下降速度 | mm / sec | 10-20 | 10-20 | 10-20 | 10-20 | 10-20 | 10-20 | 10-20 | 10-20 | 10-20 | 10-20 | 10-20 | 10-20 |
| Ascending Speed 上昇速度 | mm / sec | 300-350 | 300-350 | 300-350 | 300-350 | 300-350 | 300-350 | 300-350 | 300-350 | 300-350 | 300-350 | 300-350 | 300-350 |
| Cushion Capacity クッション能力 | ton | 30 | 50 | 70 | 90 | 100 | 140 | 180 | 200 | 240 | 350 | 400 | 500 |

※ The specification can be designed as per customer request.

※ 参考仕様の他にも、特別な設計が可能